

TORQUE MOTOR

TML0210-030

PERFORMANCE		Winding codes	3TAS	3TBS
		UNIT	FREE AIR CONVECTION	FREE AIR CONVECTION
Tp	Peak torque	Nm	127	127
Tc	Continuous torque	Nm	24.5	24.5
Ts	Stall torque	Nm	18.6	18.6
Kt	Torque constant	Nm/Arms	6.41	3.21
Ku	Back EMF constant (*)	Vrms/(rad/s)	3.71	1.85
Km	Motor constant	Nm/ \sqrt{W}	2.46	2.46
R20	Electrical resistance at 20°C (*)	Ohm	4.53	1.13
L1	Electrical inductance (*)	mH	17.3	4.32
Ip	Peak current	Arms	28.1	56.2
Ic	Continuous current	Arms	3.88	7.76
Is	Stall current	Arms	2.94	5.88
Pc	Max. continuous power dissipation	W	141	141

SPECIFICATIONS		UNIT		
Udc	Nominal input voltage	VDC	600	600
τ_{th}	Thermal time constant	s	2240	2240
Rth	Thermal resistance	K/W	0.684	0.684
2p	Number of poles	-	44	44
J	Rotor inertia	kg.m ²	0.00854	0.00854
Mr	Rotor mass	kg	1.43	1.43
Ms	Stator mass	kg	3.80	3.80
Td	Max. detent torque (average to peak)	Nm	0.60	0.60
ns	Stall speed	rpm	0.012	0.012

Notes: (*) terminal to terminal. Ambient temperature = 20 °C. Max. coil temperature = 130 °C.
 Hypothesis and tolerances are in ETEL's Handbook. Stator connected to a total surface of 0.06 m² and rotor to a total surface of 0.038 m²

Caution: Any use of the motor beyond speed/force limit could lead to hazardous voltage and serious injuries. Customer is responsible for setting safeties/limitations that will keep the motor in its safe operating area. ETEL cannot be held responsible if the motor is used in an improper way.

